

# ACCESS 165 AC

## 2-way coaxial kit

- (DFS®) Dual Fiberglass Structure cone  
**High resistance (Power, climatic conditions, humidity...)**
- Grilles new design  
**Profiled**

- Butyl surround  
**Longlife**
- Tilted tweeter on rotativ pod  
**Optimization of the sound stage**



- ABS basket with 20% of fiberglass  
**Non magnetic, non resonant**
- 25mm (1") voice coil (2 Kapton® layer)  
**High power handling**

- 85mm magnet  
**High sentivity**
- Integrated crossover (4.7 kHz)  
**Easy and quick installation**

- Dôme inversé en aluminium  
**Excellente spatialisation**

## WHAT MAKES THE DIFFERENCE

- Cone DFS® (Dual fiberglass Structure)  
(climatic and power) high resistance
- High sensitivity (Direct headunit using)
- High dynamique
- Rotativ tweeter

## TECHNICAL CHARACTERISTICS

**Woofer:** 6<sup>1</sup>/<sub>2</sub>" (165mm)

**Voice-coil diameter:** 1" (25mm)

**Voice-coil height:** 0<sup>7</sup>/<sub>16</sub>" (11mm)

**Magnet:** 3<sup>1</sup>/<sub>3</sub>" (85mm)

**Tweeter:** Aluminum inverted dome

**Crossover:** (4,7Khz) 6dB/oct

**Max. power:** 120 Watts

**Nom. power:** 60 Watts RMS

**Sensitivity (2.83V/1m):** 91dB

**Frequency response:** 60Hz – 20kHz

**Accessories:** Supplied grilles

 **Performance**  
CREATE YOUR SOUND

 **FOCAL**  
THE SPIRIT OF SOUND