KANTA N°1 Product data sheet



Kanta $N^{\circ}1$ combines performance and compactness. There's a surprise in store right from the start of your listening experience with this 2-way loudspeaker, in the form of the extent of the bass frequency response for its dimensions. Featuring Focal's latest technologies such as Flax cones, TMD suspension and NIC motor, the speaker is characterised by its precision, definition and neutrality. The performance of the latest generation IAL tweeter adds the finishing touch to the modern, ingenious design of this sound equipment. Its full potential is revealed in a room of less than 270ft^2 (25m^2).



Kanta N°1, Walnut Mat cabinet and Ivory Mat front panel, Kanta N°1, Walnut Mat cabinet and Dark Grey front panel

Key points

- Combines performance and compactness
- Extended bass frequency response
- Transducers integrating Focal's latest technologies
- Speaker drivers developed and manufactured in France by Focal
- Optional stand for optimal integration
- Numerous standard finishes

Type	2-way bass-reflex bookshelf loudspeaker
Drivers	1 x 6 ^{1/2} "(16.5cm) Flax bass-midrange with TMD suspension and NIC motor 1 ^{1/16} " (27mm) 'IAL3' pure Beryllium inverted dome tweeter
Sensitivity (2,83V/1m)	88dB
Frequency Response (+/-3dB)	46Hz - 40kHz
Low Frequency Point (- 6dB)	42Hz
Nominal Impedance	8 Ohms
Minimum Impedance	3.9 Ohms
Recommended Amplifier Power	25 - 150W
Crossover Frequency	2,400Hz
Dimensions (HxWxD)	16 ^{39/64} x 9 ^{7/32} x 15 ^{25/64} " (422 x 234 x 391mm)
Net weight (with front grille)	28.1lbs (13kg)
Packaging dimensions (HxWxD)	24 ^{1/64} x 14 ^{3/8} x 20 ^{5/64} " (610 x 365 x 510mm)
Total weight (including packaging)	33.1lbs (15kg)



