

Extremely compact & powerful 3-way, bi-amplified coaxial point source element. Dual high power 14" neodymium transducers and a unique 2" Exit throat (HF 1.75" voice coil/ MF 3.5" voice coil) coaxial neodymium compression driver.



Key features

- Extraordinary power-to-size ratio
- Three way passive system
- Unique 2" dual diaphragm compression driver
- Ergonomic design in premium birch plywood & finished in polyurea

Applications

- Outdoor events
- Large stadiums / arena
- Houses of worship
- Clubs
- Theatres
- Auditoriums

General description & specifications

The CPS-214P is a high-output extremely compact and extremely powerful 3-way, bi-amplified Coaxial Point Source element designed for large sized touring & fixed installations.

It uses two low distortion 14" (4" DUO double layer voice coil) custom speakers for the low frequencies with exclusive Malt Cross cooling technology, FEA optimized neodymium magnet circuit, aluminium demodulating ring and weatherproof cone.

For the mid/high frequencies it uses an ultra light weight 2" dual diaphragm coaxial compression. The unique voice coil technology employs a light weight copper clad aluminium wire, wound inside and out of the Kapton former to improve heat dissipation, dramatically increasing the acoustic output and reliability of the driver while minimizes the power compression.

The larger annular midrange diaphragm covers the frequency range between 300Hz and 7KHz with a smooth, linear response. The ultra light annular diaphragm for the high frequencies offers exceptional transient response with very high efficiency from 6KHz to 22KHz. With two subsystems in one each driver covers a smaller frequency range for increased power handling, high dynamic and extremely low distortion and delivers excellent phase coherence & perfect time alignment without problems of multi-source interference.

The enclosure is made from premium grade birch plywood and finished with a polyurea coating for longer durability & weather protection.

Technical Data

Components	
• LF:	LF: 2 x 14" (4" voice coil), neodymium magnet, 2000W (AES).
• MF/HF:	MF: 3.5" (90mm) voice coil, 150W (AES). HF: 1.5" (44,4 mm) voice coil, 80W (AES)
Frequency range	55 Hz - 22 KHz (-6dB)
Coverage	Rotatable 60°H x 40°V
Max SPL*	Low: 137 dB / 143 dB - Mid/High: 139,5 dB / 142,6 dB
Sensitivity	LF: 101 dB (1w/1m) MF/HF: 118 dB
Impedance	Low section: 4 Ω (8 + 8 Ω) Mid/high section: 8 Ω
Crossover	Mid/high: 6300 Hz - Low/mid: 500 Hz
Speakon connection	+1 -1 Low / +2 -2 Mid/high
Finish	Polyurea coating, high grade resistant paint
Material	15 mm Premium birch plywood
Dimensions	900 x 420 x 515 mm (H x W x D)
Weight	47 Kg (103.6 lbs)

*Calculated maximum SPL based on rated peak power and measured sensitivity.

Dimensional Drawing

