

Ultra-compact, self powered (class D switch mode power supply with PFC), omni-directional subwoofer cabinet.



### Key features

- Compact & versatile
- Powered with Class D
- DSP presets for wide applications
- Easy to use, easy to install
- Portable
- Available in black or white

### Applications

- PA system
- Clubs & theatres
- Houses of worship
- Solo artists, band, DJ
- Public address
- Commercial complex

## General description & specifications

The Ionic-12S is a powered subwoofer enclosure part of the Ionic series. The Ionic cabinets are compact, modular and powerful and the complete series includes two subwoofers and two column models.

The Ionic-12S uses 1 x 12" (3" voice coil) neodymium transducers offering an ultra compact subwoofer enclosure with 127dB SPL.


The power module (Class D with switching power supply) includes a Digital Signal Processor which offers different presets to cover a wide range of sound applications complementing the column speakers.

Ionic-12S provides quick and easy set ups for both fixed installations and portable applications.




## Technical Data

Components	1 x 12" speaker with 3" voice coil
Frequency range	40 Hz - 250 Hz (-10dB)
Frequency response	46 Hz - 250 Hz (± 3dB)
Max SPL	127 dB
Coverage	Omnidirectional
Power	1400W Class D with switching power supply & PFC LF amplifier: 1 x 700 W
Speaker Output Amplifier	1 x 700 W @ 8 Ω
Processing	Internal Lynx Processor DSPB-FL 96 KHz / 64 bit double-precision, DSP with FIR filter linear phase
Control	User control interface with 2.8" IPS screen
Control Connections	Ethernet (OCS) / USB (DSP programming)
Input	Analog / AES3 (optional)
AC Power	85 - 270V. 50/60 Hz with PFC
AC Connections	16A Neutrik powerCon TRUE1 TOP with looping output
Finish	Polyurea coating, black colour
Material	15 mm premium birch plywood
Dimensions	407 x 440 x 520 mm (H x W x D)
Weight	23 kg (50.6 lbs)

## Dimensional Drawing



## Accessories

	SV-I2S	Sub adaptor for satellite
	FD-IONIC12S	Nylon Protection Cover for Ionic-12S
	VSM-V2	M20 connector plate for M20 pole support TU-C02