

# 18HP1042

18" - 1000 W - 98 dB - 8 Ohm



## NOMINAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Overall Diameter	460 mm (18.11 in)
Bolt Circle Diameter	440 mm (17.32 in)
Baffle Cutout Diameter	422 mm (16.61 in)
Depth	202 mm (7.95 in)
Flange and Gasket Thickness	14 mm (0.55 in)
<b>Net Weight</b>	<b>6.7 kg (14.8 lb)</b>
Shipping Box (Single Carton Box)	503 x 500 x 258 mm (19.8 x 19.7 x 10.2 in)
Shipping Weight	7.8 kg (17.2 lb)

## PART NUMBER

Push Terminals - 8 Ohm Version 04604200

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.6 Ohm
AES Power Handling (1)	1000 W
<b>Maximum Power Handling (2)</b>	<b>2000 W</b>
<b>Sensitivity (1W/1m)</b>	<b>98 dB</b>
Frequency Range	38-2500 Hz
<b>Voice Coil Diameter</b>	<b>100 mm (4 in)</b>
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	22 mm (0.87 in)
<b>Magnetic Gap Depth</b>	<b>12 mm (0.47 in)</b>
Flux Density	1.3 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	5.8 dm <sup>3</sup> (0.205 ft <sup>3</sup> )
Spider Profile	2x non-adjacent symmetrical constant height waves

## THIELE & SMALL PARAMETERS

Fs	38 Hz
Re	5.5 Ohm
Qes	0.43
Qms	10.3
Qts	0.41
Vas	191.9 dm <sup>3</sup> (6.78 ft <sup>3</sup> )
Sd	1212 cm <sup>2</sup> (187.86 in <sup>2</sup> )
Xmax (4)	9.00 mm
Xdamage (5)	17.5 mm
Mms	187.5 g
Bl	24.5 N/A
Le	1.26 mH
Mmd	139.8 g
Cms	0.08 mm/N
Rms	4.58 kg/s
Eta Zero	2.49 %
EBP	88 Hz

