

# 18XL2000

18" - 2000 W - 97 dB - 8 Ohm



## NOMINAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Overall Diameter	460 mm (18.11 in)
Bolt Circle Diameter	440 mm (17.32 in)
Baffle Cutout Diameter	422 mm (16.61 in)
Depth	227 mm (8.94 in)
Flange and Gasket Thickness	14 mm (0.55 in)
<b>Net Weight</b>	<b>11.3 kg (24.9 lb)</b>
Shipping Box (Single Carton Box)	490 x 485 x 275 mm (19.3 x 19.1 x 10.8 in)
Shipping Weight	12.8 kg (28.2 lb)

## PART NUMBER

Push Terminals - 8 Ohm Version 04604293

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	7 Ohm
AES Power Handling (1)	2000 W
<b>Maximum Power Handling (2)</b>	<b>4000 W</b>
<b>Sensitivity (1W/1m)</b>	<b>97 dB</b>
Frequency Range	30-1600 Hz
<b>Voice Coil Diameter</b>	<b>118 mm (4.65 in)</b>
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	37.3 mm (1.47 in)
<b>Magnetic Gap Depth</b>	<b>14 mm (0.55 in)</b>
Flux Density	1.2 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Double AI Dem. Ring
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	7.3 dm <sup>3</sup> (0.258 ft <sup>3</sup> )
Spider Profile	2x non-adjacent symmetrical constant height waves

## THIELE & SMALL PARAMETERS

Fs	28 Hz
Re	5.3 Ohm
Qes	0.28
Qms	10.1
Qts	0.27
Vas	232.1 dm <sup>3</sup> (8.20 ft <sup>3</sup> )
Sd	1213 cm <sup>2</sup> (188.02 in <sup>2</sup> )
Xmax (4)	16.32 mm
Xdamage (5)	33 mm
Mms	286.0 g
Bl	30.8 N/A
Le	1.45 mH
Mmd	238.3 g
Cms	0.11 mm/N
Rms	5.0 kg/s
Eta Zero	1.8 %
EBP	100 Hz

