

10FH500



10" - 500 W - 96 dB - 4 Ohm

NOMINAL SPECIFICATIONS

| | |
|----------------------------------|---|
| Nominal Diameter | 250 mm (10 in) |
| Overall Diameter | 261 mm (10.28 in) |
| Bolt Circle Diameter | 246 mm (9.69 in) |
| Baffle Cutout Diameter | 232 mm (9.13 in) |
| Depth | 141.3 mm (5.56 in) |
| Flange and Gasket Thickness | 12.5 mm (0.49 in) |
| Net Weight | 3.4 kg (7.5 lb) |
| Shipping Box (Single Carton Box) | 294 x 290 x 203 mm (11.6 x 11.4 x 7.8 in) |
| Shipping Weight | 4 kg (8.8 lb) |

PART NUMBER

| | |
|--------------------------------|----------|
| Push Terminals - 4 Ohm Version | 02504043 |
|--------------------------------|----------|

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

| | |
|--------------------------------------|--|
| Nominal Impedance | 4 Ohm |
| Minimum Impedance | 4 Ohm |
| AES Power Handling (1) | 500 W |
| Maximum Power Handling (2) | 1000 W |
| Sensitivity (1W/1m) | 96 dB |
| Frequency Range | 60-4000 Hz |
| Voice Coil Diameter | 77 mm (3 in) |
| Winding Material | Al |
| Former Material | Glass Fiber |
| Winding Depth | 18 mm (0.71 in) |
| Magnetic Gap Depth | 10.5 mm (0.41 in) |
| Flux Density | 1.2 T |
| Magnet | Neodymium Slug |
| Basket Material | Aluminum |
| Demodulation | No |
| Cone Surround (3) | Triple Roll |
| NET Air Volume filled by Loudspeaker | 1.6 dm ³ (0.057 ft ³) |
| Spider Profile | 1x constant height waves |

THIELE & SMALL PARAMETERS

| | |
|-------------|--|
| Fs | 60 Hz |
| Re | 3.3 Ohm |
| Qes | 0.26 |
| Qms | 6.2 |
| Qts | 0.25 |
| Vas | 24.2 dm ³ (0.85 ft ³) |
| Sd | 351 cm ² (54.41 in ²) |
| Xmax (4) | 7.25 mm |
| Xdamage (5) | 12.5 mm |
| Mms | 50.1 g |
| Bl | 15.5 N/A |
| Le | 0.64 mH |
| Mmd | 42.7 g |
| Cms | 0.14 mm/N |
| Rms | 3.0 kg/s |
| Eta Zero | 1.95 % |
| EBP | 231 Hz |

