CAMERA HEAD Ø 3,9 mm flexible - 1 m

for RC3 Inspection camera

Item no.: 21000





DATA	
ITEM NO.:	21000
WEIGHT NET	0,03 kg
DIMENSION	L 1060,1 mm x B 12 mm x H 9 mm
DIAMETER	3,9 mm
LENGTH	1 m
INTEGRATED LIGHTING	6 x LED (dimmable)
IMAGE RESOLUTION	1920 x 1080 und 1280 x 720 pixels
ANGLE OF VIEW	80 °
FOCUS DISTANCE	20 - 80 mm
LENS	3P + IR (infrared)
CASE	Stainless steel
PROTECTION CLASS	IP67
EAN-CODE	9120045477979

ADVANTAGES

- Flexible gooseneck for individual viewing angle adjustment
- Suitable for RC3 inspection camera
- Protection class IP67
- Viewing angle 80 degrees
- 3.9 mm camera
- 6 integrated LEDs (dimmable)
- For areas that are difficult to access
- High image quality

DESCRIPTION

This 3.9 mm endoscope camera combines state-of-the-art sensor technology with a robust, semi-rigid 1 metre cable and 30 mm spring tube. It enables detailed inspections in hard-to-reach areas and offers a reliable solution for demanding applications thanks to the front camera and excellent image quality.

Waterproof and robust: Ideal for use in damp environments, the camera is waterproof to IP67 and made from durable stainless steel.

High image quality: Razor-sharp images with a resolution of 1920×1080 or 1280×720 pixels.

3P+IR lens: consists of three precision-ground lens elements for maximum clarity and sharpness. The integrated infrared (IR) filter minimises unwanted infrared rays, improving colour fidelity and image quality, even in challenging lighting conditions.

Optimum field of view: With a viewing angle of 80 degrees and a frame rate of 15 to 30 frames per second, you won't miss any details, whether for inspections or precise documentation. Focus distance 20 mm - 80 mm **LED illumination:** Six integrated LEDs (dimmable) with a colour temperature of 5500-6500 K ensure optimum lighting conditions and a clear view, even in dark areas.

Durable: Toughened glass protective screen protects the camera and ensures long-lasting use

Scope of supply: 1 x Endoscope camera 3.9 mm, length 1 meter

