CAMERA HEAD TRIPLE LENS Ø 8 mm flexible - 1 m

for RC3 Inspections camera Item no.: **21002**





DATA

| ITEM NO.: | 21002 |
|---------------------|---|
| WEIGHT NET | 0,043 kg |
| DIMENSION | L 1060 mm x B 12 mm x H 8 mm |
| DIAMETER | 8 mm |
| LENGTH | 1 m |
| INTEGRATED LIGHTING | 8 x LED (dimmable) |
| IMAGE RESOLUTION | 1920 x 1080 und 1280 x 720 Pixel |
| ANGLE OF VIEW | 80 ° |
| FOCUS DISTANCE | Front camera 30 - 80 mm - Side camera 20 - 50 mm |
| PROTECTION CLASS | IP67 |
| EAN-CODE | 9120045477979 |
| | |

DESCRIPTION

The endoscope camera with a triple lens (1 x front camera and 2 x side cameras) and an 8mm diameter is the ideal choice for precise and versatile inspection work. Thanks to the semi-flexible 1m cable with integrated 30mm spring tube, even hard-to-reach areas can be inspected with ease. With the two side cameras, this camera module offers maximum flexibility. Thanks to the versatile depth of field of the front and side cameras, even the smallest details are clearly visible.

Image resolution: Selectable between 1920 x 1080 and 1280 x 720 pixels for different applications.

Waterproof: Ideal for use in damp environments. The camera is IP67 waterproof.

LED lighting: 8 powerful LEDs (dimmable) with a colour temperature of 5500-6500K ensure optimum visibility in dark environments

Image angle: Generous 80 degrees for wider inspection angles

Frame rate: Smooth videos with 15-30 FPS for a detailed real-time display **Depth of field:** Front camera: 30-80 mm | 2 x side cameras: 20-50 mm - for razor-sharp images from different distances

Scope of supply: 1 x Endoscope camera 8 mm with triple lens, length 1 meter, 1 x hook, 1 x magnet, 1 x lens protection cap

ADVANTAGES

- Flexible gooseneck for individual viewing angle adjustment
- Suitable for RC3 inspection camera
- Protection class IP67
- Viewing angle 80 degrees
- 8 mm triple lens
 (1 x front and 2 x side camera
- 8 integrated LEDs (dimmable)
- For areas that are difficult to access
- High image quality

INFORMATION

